

Specifications

Item no.	temperature	consumption	height	weight	tube	head	load	DIN	GS	Natural gas	Bottle gas	safety-base
	°C	l/h	mm	g	Ø mm	Ø mm	kW					+ 38 g
1000	1500	110	155	210	14	17	1,25	+	+	+		•
1001	1540	55	155	210	14	17	1,35	+	+		+	•
1010	1500	110	155	220	14	17	1			+		•
1010/1	1500	115	155	220	14	17	1	+	+	+		•
1011	1550	55	155	220	14	17	1,7				+	•
1011/1	1550	55	155	220	14	17	1,7	+	+		+	•
1020	1500	110	155	220	14	17	1,1	+	+	+		•
1021	1520	55	155	220	14	17	1,25	+	+		+	•
1030	1500	110	155	225	14	17	1,1			+		•
1030/1	1500	110	155	225	14	17	1,1	+	+	+		•
1031	1520	50	155	225	14	17	1,25				+	•
1031/1	1520	50	155	225	14	17	1,25	+	+		+	•
1040	1500	100	155	245	14	17	1,1			+		•
1040/1	1500	100	155	245	14	17	1,1	+	+	+		•
1041	1520	55	155	245	14	17	1,25				+	•
1041/1	1520	55	155	245	14	17	1,25	+	+		+	•
1045/1	1480	90	155	235	14	17	1,1	+	+	+		•
1046/1	1500	55	155	235	14	17	1,25	+	+		+	•
1050	1460	110	170	270	13	17	1,2			+		•
1050	1510	35	170	270	13	17	1,2				+	•
1060	1600	120	125	120	14	17	1,3			+		•
1061	1630	42	125	120	14	17	1				+	•
1110	1310	35	100	115	7	11	0,4			+		•
1111	1320	20	100	115	7	11	0,3				+	•
1200	1550	115	155	245	14	17	1,5			+		•
1201	1560	65	155	245	14	17	1,3				+	•
1210	1520	125	155	260	14	17	1,3			+		•
1210/1	1520	125	155	260	14	17	1,3	+	+	+		•
1211	1560	65	155	260	14	17	1,5				+	•
1211/1	1560	65	155	260	14	17	1,5	+	+		+	•
1220	1530	110	155	260	14	17	1,25	+	+	+		•
1221	1530	65	155	260	14	17	1,5	+	+		+	•
1230	1530	110	155	265	14	17	1,25			+		•
1230/1	1530	110	155	265	14	17	1,25	+	+	+		•

Specifications

Item no.	temperature	consumption	height	weight	tube	head	load	DIN	GS	Natural gas	Bottle gas	safety-base
	°C	l/h	mm	g	Ø mm	Ø mm	kW					+ 38 g
1231	1550	55	155	265	14	17	1,5				+	•
1231/1	1550	55	155	265	14	17	1,5	+	+		+	•
1240	1480	100	155	280	14	17	1,25			+		•
1241	1530	65	155	280	14	17	1,5				+	•
1245/1	1500	100	155	270	14	17	1,25	+	+	+		•
1246/1	1540	60	155	270	14	17	1,5	+	+		+	•
1300	1520	200	165	330	19	32	2,3			+		•
1300/1	1550	220	165	330	19	32	2,3	+	+	+		•
1301	1600	85	165	330	19	32	2,5				+	•
1320	1500	140	155	255	14	17	1,6			+		
1320	1540	50	155	255	14	17	1,7				+	
1330	1520	110	160	370	13	17	1,7		+	+		
1330/1	1520	110	160	400	13	17	1,5		+	+		
1331	1550	65	160	370	13	17	2		+		+	
1331/1	1550	65	160	400	13	17	1,7		+		+	
1340	1520	110	160	370	13	17	1,7		+	+		
1341	1550	65	160	370	13	17	2		+		+	
1350	1490	120	200	335	28	32	2			+		
1350	1320	60	200	335	28	32	1,9				+	
1360	1500	120	200	335	28	32	1,8			+		•
1361	1350	75	200	335	28	32	2				+	•
1420	1620	0,13	232	545	14	17	1,4	+	+			
1421	1620	0,13	140	190	14	17	1,4					
1422	1530	0,13	85	145	10	20	1,3					
1423	1440	0,1	60	145		15	1					
1424	1550	0,15	50	200		20	1,5					
1425	1620	0,13	160	660	14	17	1,4	+	+			
1430			92	355		104						
1500	870	0,04	50	75								